


Owl 640 N

640 x 512, VIS-SWIR Camera



Key Features and Benefits


- **640 x 512, 15 μ m pitch VIS-SWIR sensor**
HD resolution imaging from 0.6 μ m to 1.7 μ m
- **On-board Intelligent 3 point NUC and ALC**
Real time, optimal video in all light conditions
- **Designed for Harsh environments**
High Shock, Vibration and extreme temperature resistance
- **Global Shutter**
120Hz full frame video, with no distortion (ideal for triggering)
- **Low Noise Electronics**
No artificial noise added, optimising low light capability

Resolution	640 x 512
Frame Rate	Up to 120Hz
Camera Link	14 bit
Wavelength Range	VIS-SWIR

Specification for Owl 640 N

Sensor	InGaAs PIN-Photodiode
Active Pixel	640 x 512
Pixel Pitch	15 µm x 15µm
Active Area	9.6mm x 7.68mm
Spectral Response ¹	0.6µm to 1.7µm
Readout Noise (RMS)	LG: <175e- (150e- typical) HG: <22e- (18e- typical)
Peak Quantum Efficiency	>90% @1.3µm
Full Well Capacity	Low Gain: >250ke- High Gain: >10k-
Pixel Operability	>99.5%
Digital Output Format	14 bit Camera Link (Base Configuration / SDR)
Exposure Time	50µs to 26.8µs ⁷
Shutter Mode	Global Shutter
Frame Rate	Up to 120Hz
Optical Interface	C Mount
Dynamic Range (Typ)	LG: 62dB HG: 55dB
Trigger Interface	Trigger IN and OUT - TTL compatible
Power Supply	12V DC ±0.5V
TE Cooling	Active
Image Correction	3 point NUC (offset, Gain & Dark Current) + pixel correction
Functions controlled by serial communication	Exposure, intelligent AGC, Non Uniformity Correction, Gamma, Pk/Av, TEC, ALC ROI
Camera Power Consumption ²	<4W (TEC ON, NUC ON)
Operating Temperature ³	-20° C to +55° C
Storage Temperature	-30° C to +60° C
Dimensions (excluding standard mounting) ⁴	69.4mm x 50.00mm x 50.00mm
Weight	242g

Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors. This product is under the export control of the UK government and may be subject to a single individual export license before shipment. Note 1: Optional filters available: Low, High or bandpass Note 2: Measured in an ambient of 25° C with adequate heat sinking. For more detailed power consumption values, please refer to the user manual. Note 3: Extended Operating Temperature range on request Note 4: Dimensions include all connector parts on camera interface Note 5: Longer CL cable available Note 6: Please consult us to check our range of lenses. Note 7: LG Mode



*Data Supplied by Sensor Manufacturer

Specification for Owl 640 N

Camera

OWL 640 N Digital Camera	NO1.7-VS-CL-640
Power Supply Cable	RPL-HR4-K

Optional Accessories

Mini PC with XCAP STD and Frame Grabber	RPL-PC-mf2280
Thunderbolt Frame Grabber	RPL-mf2280
EPIX® EB1 Frame Grabber	RPL-EPIX-EB1
EPIX® XCAP STD Software	RPL-XCAP-STD
MDR-SDR CameraLink Cable ⁵ (2m)	RPL-MCL-CBL-2M
Optical SWIR lenses ⁶	RPL-xx-xxx

Applications

- 860,1064 & 1550nm laser line detection
- Active Imaging
- Airborne Payload
- Handheld Systems
- Imaging through Fog
- Range Finding
- Vision Enhancement
- Hyperspectral Imaging
- Semi Conductor Inspection
- Solar Cell Inspection

For detailed technical drawings, volume pricing or to set up a demo, contact us at sales@raptorphotronics.com

Document#: INOW1.7-VS-CL-640N-0425